
	FIXTURE SCHEDU	LE			
SYM.	DESCRIPTION	HOT	COLD	WASTE	VENT
(S-I)	CLASSROOM SINK - ELKAY PSDKAD25ITC STAINLESS STEEL SINK WITH LK2085I3L GOOSENECK FAUCET, LKII4IA FLEX GUARD BUBBLER, LK-35 STRAINER, I/2" STOPS AND I-I/2" P-TRAP. PROVIDE RIGHT OR LEFT HANDLE CONFIGURATION AS REQUIRED. (SEE PLANS)		1/2"	I-I/2"	I-I/2"
DF-I)	BI-LEVEL DRINKING FOUNTAIN - ELKAY EZSTL&C WITH FRONT AND SIDE EASY TOUCH CONTROLS, FLEXI-GUARD BUBBLERS, I/2" STOP VALVE AND (2) I-I/2" P-TRAPS. I20/60/I.		(2) 1/2"	(2) I-I/2"	(2) I-I/2"
EM-I	EMERGENCY EYEWASH - HAWS MODEL 7260B WALL MOUNTED EYE WASH WITH II" PLASTIC RECEPTOR, ALUMINUM WALL BRACKET, AND STAY-OPEN VALVE. RUN I-I/2" WASTE LINE TO ADJACENT SERVICE SINK. REFER TO DETAIL B/PI.2.		1/2"	I-I/2" TO P-I2 SINK	
FD-D	2" FLOOR DRAIN - ZURN Z-415 WITH 5"\$ TYPE 'B' STRAINER AND 2" DEEP SEAL P-TRAP. PROVIDE WITH Z-1022 TRAP PRIMER.			2"	2"
FD-2	4" FLOOR DRAIN - ZURN Z-415 WITH 8"\$ TYPE 'B' NICKEL BRONZE STRAINER AND 4" DEEP SEAL P-TRAP. PROVIDE WITH Z-1022 TRAP PRIMER.			4"	2"
F5-I)	4" FLOOR SINK W/ I/2 GRATE - ZURN Z-1900-2 WITH I/2 GRATE, DOME STRAINER, WHITE ENAMEL FINISH AND 4" DEEP SEAL P-TRAP.			4"	2"
HB-I	EXTERIOR HOSE BIBB - ZURN Z-1310 "ECOLOTROL" WITH REMOVABLE KEY, VACUUM BREAKER AND AUTOMATIC DRAIN. LENGTH TO SUIT WALL THICKNESS.		3/4"		
(HB-2)	INTERIOR HOSE BIBB - WOODFORD MODEL 24P-1/2 WITH VACUUM BREAKER AND REMOVABLE CHROME TEE HANDLE.		1/2"		
∰-3)	HOSE BIBB FAUCET - WFICSHER 29556 SILL FAUCET, I/2" F INLET, 3/4" HOSE THREAD, VACUUM BREAKER, LEVER STYLE HANDLE. MOUNT ABOVE MOP SINK AT 36" ABOVE FLOOR.		1/2"		
(Æ	ICE MAKER CONNECTION BOX - GUY GRAY MODEL BIM875 RECESSED WALL MOUNTED UTILITY BOX WITH I/2" COLD WATER SUPPLY COMPLETE WITH SHUT-OFF VALVE. COORDINATE MOUNTING HEIGHT OF BOX WITH EQUIPMENT BEING FURNISHED.		1/2"		
<u>J</u> 5-I)	FLOOR MOUNTED SERVICE SINK - KOHLER K-6710 "WHITBY WITH K-8940 WIRE RIM GUARD, K-8928 FAUCET ASSEMBLY AND K-9147 DRAIN ASSEMBLY WITH 2" DEEP SEAL P-TRAP.	1/2"	1/2"	2"	2"
J5-2)	FLOOR MOUNTED SERVICE SINK - FIAT TSB-700 (24x36) PRE-CAST TERRAZZO FLOOR MOUNTED SINK COMPLETE WITH PERFORATED STRAINER AND 2" DEEP SEAL P-TRAP. PROVIDE AND INSTALL FISCHER 8253 WALL MOUNTED FAUCET WITH LEVER HANDLES, VACUUM BREAKER, WALL SUPPORT, PAIL HOOK, 30" RUBBER HOSE, AND WALL MOUNTED HOSE BRACKET.	1/2"	1/2"	2"	2"
(K-I)	HAND SINK AND FAUCET (KIT. EQ. #KI & KI.I) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH STOPS AND I-I/2" VENT AND WASTE LINES WITH P-TRAP.	l/2"	1/2"	I-I/2"	I-I/2"
(K-7)	PREP TABLE WITH SINK AND FAUCET (KIT. EQ. #K7 & K7.I) - BY KIT. EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH STOPS AND I-I/2" YENT AND INDIRECT DRAIN LINE TO NEAREST FLOOR SINK.	l/2"	1/2"	I-I/2" TO FLOOR SINK	I-I/2"

C) (1) 1	FIXTURE SCHEDI	T			
SYM.	DESCRIPTION DESCRIPTION	HOT	COLD	WASTE 2"	VENT
(K-10)	EYEWASH STATION (KIT. EQ. #KIO) - BY KIT. EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" COLD WATER LINE WITH STOP AND 2" VENT AND WASTE LINE WITH P-TRAP.		1/2	2	2
K-II)	GARBAGE DISPOSER (KIT. EQ. #KII) - BY KIT. EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" COLD WATER LINE WITH STOP AND 2" VENT AND WASTE LINE WITH P-TRAP.		1/2"	2"	2"
(K-15)	HAND SINK AND FAUCET (KIT. EQ. #KI5 & KI5.I) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH STOPS AND I-I/2" VENT AND WASTE LINES WITH P-TRAP.	1/2"	1/2"	I-I/2"	I-I/2
(K-17)	MALK-IN COOLER & FREEZER (KIT. EQ. #KT) - BY KITCHEN EQUIP. CONTRACTOR. RUN 3/4" DRAIN LINE FROM EVAPORATIVE COOLERS TO NEAREST FLOOR SINK. PROVIDE HEAT TAPE ON LINES AS REQUIRED.			3/4" TO FLOOR SINK	
(K-3T) (K-38)	CONVECTION OVEN (KIT. EQ. #K37 & K38) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT (2) 3/4" GAS LINE WITH SHUT-OFF VALVE. CONNECT WITH FLEXIBLE HOSE CONNECTION (144,000 BTU)				
(K-39)	GAS RANGE (KIT. EQ. #K39) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I" GAS LINE WITH SHUT-OFF VALVE. CONNECT WITH FLEXIBLE HOSE CONNECTION. (177,000 BTU)				
K-41)	CONVECTION STEAMER (KIT. EQ. #K4I) - BY KITCHEN EQUIP. CONTRACTOR ROUGH-IN AND CONNECT I/2" COLD WATER LINE WITH SHUT-OFF VALVE TO WALL MOUNTED FILTER. RUN 2" DRAIN LINES TO NEAREST FLOOR SINK.		1/2"	2" TO FLOOR SINK	
(K-43)	TILT SKILLET AND FILL FAUCET (KIT. EQ. #K43) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH SHUT-OFF VALVES.	1/2"	1/2"		
(K-45)	TILT SKILLET AND FILL FAUCET (KIT. EQ. #45) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH SHUT-OFF VALVES.	1/2"	1/2"		
(K-48)	WORK TABLE WITH SINK AND FUACET (KIT. EQ. #K48 & K48.I) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH SHUT-OFF VALVES. RUN I-I/2" WASTE LINE TO NEAREST FLOOR SINK.	1/2"	1/2"	I-I/2" TO FLOOR SINK	
(K-51)	COLD FOOD BUFFET UNIT (KIT. EQ. #K5I) - BY KIT. EQUIP. CONTRACTOR. RUN DRAIN LINE TO NEAREST FLOOR SINK.FIELD VERIFY DRAIN LINE SIZE(S).			TO FLOOR SINK	
K-54)	HOT FOOD BUFFET UNIT (KIT. EQ. #K54) - BY KIT. EQUIP. CONTRACTOR. RUN DRAIN LINE TO NEAREST FLOOR SINK. FIELD VERIFY DRAIN LINE SIZE(5).			TO FLOOR SINK	
(K-58)	HOT FOOD BUFFET UNIT (KIT. EQ. #K58) - BY KIT. EQUIP. CONTRACTOR. RUN DRAIN LINE TO NEAREST FLOOR SINK. FIELD VERIFY DRAIN LINE SIZE(S).			TO FLOOR SINK	
(K-61)	COLD FOOD BUFFET UNIT (KIT. EQ. #K61) - BY KIT.			ТО	

SYM.	FIXTURE SCHEDU DESCRIPTION	НОТ	COLD	WASTE	VEN
(K-63)	MILK COOLER (KIT. EQ. #K63) - BY KIT. EQUIP. CONTRACTOR. RUN DRAIN LINE TO NEAREST FLOOR SINK.FIELD VERIFY DRAIN LINE SIZE(S).			TO FLOOR SINK	
(K-71)	DISHWASHER, FILTER, AND BOOSTER HEATER (KIT. EQ. #KTI & KTI.I) - BY KITCHEN EQUIPMENT CONTRACTOR. ROUGH-IN AND CONNECT 3/4" HOT WATER LINE TO WATER FILER AND FROM BOOSTER HEATER TO DISHWASHER. RUN DRAIN LINE FROM DISHWASHER TO NEAREST FLOOR SINK.	3/4"		TO FLOOR SINK	
(K-14)	DISHTABLE WITH 3 COMPARTMENT SINK AND PRE-RINSE SPRAY NOZZLE (KIT. EQ. #K74 & 74.I) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT (I) I/2" HOT AND COLD WATER LINES TO PRE-RINSE FAUCET AND (I) 3/4" HOT AND COLD WATER LINES WITH SHUT-OFF VALVES TO (2) FAUCETS. RUN I-I/2" WASTE LINE TO NEAREST FLOOR SINK.	(I) I/2" (I) 3/4"	(I) I/2" (I) 3/4"		
(K-75)	GARBAGE DISPOSER (KIT. EQ. #K75) - BY KIT. EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" COLD WATER LINE WITH STOP AND 2" VENT AND WASTE LINE WITH P-TRAP.		l/2"	2"	2'
(K-79)	HAND SINK AND FAUCET (KIT. EQ. #K79) - BY KITCHEN EQUIP. CONTRACTOR. ROUGH-IN AND CONNECT I/2" HOT AND COLD WATER LINES WITH STOPS AND I-I/2" VENT AND WASTE LINES WITH P-TRAP.	I/2"	1/2"	I-I/2"	I-I/2
[L-]	ADA WALL HUNG LAVATORY - KOHLER K-2032 "GREENWICH" (SIZE 20x18) WITH K-13885 OFFSET OPEN GRID STRAINER, SLOAN EBF-85 OPTIMA AUTO FAUCET, WALL CARRIER, I/2" STOPS & I-I/2" P-TRAP. PROVIDE INSULATING JACKET ON WATER & WASTE PIPING.	l/2"	1/2"	I-I/2"	I-I/2
(L-2)	KINDERGARTEN WALL HUNG LAVATORY - KOHLER K-2032 "GREENWICH" (SIZE 20xI8) WITH K-17I5 OPEN GRID STRAINER, SLAON EBF-85 OPTIMA AUTO FAUCET, I/2" STOPS, WALL CARRIER AND I-I/2" P-TRAP. SEE ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHT.	l/2"	1/2"	I-I/2"	I-I/2
(5-1)	DOUBLE COMPARTMENT SINK - ELKAY LR-33I9 STAINLESS STEEL SINK WITH (2) LK-99 STRAINERS, MOEN 7200 SINGLE LEVER FAUCET, I/2" STOPS AND I-I/2" P-TRAP.	1/2"	1/2"	I-I/2"	I-I/2
(H-1)	ADA PRE-FAB SHOWER STALL - LASCO MODEL 6030CFS COMPLETE WITH GRAB BARS, FOLD-UP SEAT, HAND-HELD SHOWER ASSEMBLY WITH SLIDE BAR, PRESSURE BALANCING MIXING VALVE, SOAP DISH, CURTAIN ROD AND SHOWER CURTAIN, AND	I/2"	I/2"	2"	2'
(E)-I)	PERFORATED DRAIN WITH 2" DEEP SEAL P-TRAP. MOUNT SHOWER HEAD AND FAUCET AT END OF UNIT. FLOOR TROUGH - PROVIDE AND INSTALL ZURN Z-890-2EI-30 (30x6) TROUGH DRAIN WITH STAINLESS STEEL SUBWAY GRATING AND END CAPS. CONNECT 2" DRAIN LINE TO BOTTOM OF TROUGH WITH DEEP SEAL P-TRAP.			2"	2'
(TP-2)	FLOOR TROUGH - PROVIDE AND INSTALL EAGLE GROUP ASFT-2430-SG 'ANTI-SPLASH' TROUGH WITH STAINLESS STEEL SUBWAY GRATING, 6" DEEP TROUGH PAN WITH BUILT-IN PITCH TOWARD DRAIN. PROVIDE REMOVABLE PERFORATED BASKET. CONNECT 3" DRAIN LINE TO BOTTOM OF TROUGH WITH DEEP SEAL P-TRAP.			3"	3'
[P-]	SINGLE DRAIN TRAP PRIMER - ZURN Z-1022XL IN-LINE PRIMER. MOUNT RECESSED IN WALL BELOW SINK WHERE SHOWN ON PLANS. RUN 1/2" COLD WATER LINES BELOW FLOOR TO SINGLE FLOOR DRAIN. REFER TO DETAIL B/PO.3 FOR TYPICAL INSTALLATION.		I/2"		
(P-2)	MULTIPLE DRAIN TRAP PRIMER - ZURN Z-1020XL-5-CW ELECTRONIC TRAP PRIMER SYSTEM. MOUNT RECESSED IN WALL WITH COVER. RUN I/2" COLD WATER LINE TO EACH TRAP AS SHOWN ON FLOOR PLANS. REFER TO DETAIL A/PO.3 FOR TYPICAL INSTALLATION.		3/4"		
TP-3	MULTIPLE DRAIN TRAP PRIMER - ZURN Z-1020XL-10-CW ELECTRONIC TRAP PRIMER SYSTEM. MOUNT RECESSED IN WALL WITH COVER. RUN 1/2" COLD WATER LINE TO EACH TRAP AS SHOWN ON FLOOR PLANS. REFER TO DETAIL A/PO.3 FOR TYPICAL INSTALLATION.		3/4"		

	FIXTURE SCHE				
SYM.	DESCRIPTION	HOT	COLD	WASTE	VEN
U-I	URINAL - KOHLER MODEL 4984-T "FRESHMAN" WITH SLOAN 8186 OPTIMA PLUS BATTERY POWERED SENSOR FLUSH VALVE AND WALL CARRIER. SEE ARCHITECTURAL DRAWINGS FOR MOUNTING HEIGHT		3/4"	2"	2"
W-I	MASHING MACHINE HOOK-UP - PROVIDE AND INSTALL GUY- GRAY MODEL NWBBED200TS COMBINATION BOX COMPLETE WITH 2" WASTE LINE WITH P-TRAP, I/2" HOT AND COLD WATER SUPPLIES (FROM TOP) AND ELECTRICAL OUTLETS (STANDARD I20V AND 240V OUTLETS - SEE ELECTRICAL DRAWINGS) REFER TO DETAIL C/PI.2 FOR TYPICAL LINE CONNECTIONS.	I/2"	1/2"	2"	2"
(WB-I)	WASH BASIN - BRADLEY MODEL MF2949 'TERREON QUADRA-FOUNT' WALL HUNG BASIN WITH SINGLE TEMPERED LINE, PRE- ASSEMBLED THERMOSTATIC MIXING VALVE AND INFRARED SENSORS.	I/2"	1/2"	I-I/2"	I-I/2
(WC-I)	ADA WATER CLOSET - KOHLER K-4368 "HIGHCLIFF" WITH ELONGATED BOWL, K-4670C WHITE OPEN FRONT SEAT, SLOAN 8III OPTIMA PLUS BATTERY POWERED SENSOR FLUSH VALVE AND CHINA BOLT CAPS		l"	4"	2"
(W-2)	WATER CLOSET - KOHLER K-4350 "WELLCOMME" W ELONGATED BOWL, K-4670-C WHITE OPEN FRONT SEAT, SLOAN 8III OPTIMA PLUS BATTERY POWERED SENSOR FLUSH VALVE AND CHINA BOLT CAPS.		l"	4"	2"
WH-I)	ELECTRIC WATER HEATER - A.O. SMITH EJCT-20 WITH 20 GALLON TANK, SINGLE 2.5 KM ELEMENT AND T&P RELIEF VALVE AND AMTROL ST-5 EXPANSION TANK. MOUNT ON MEZZANINE LEVEL WITH SHEET METAL DRAIN PAN.	3/4"	3/4"		
WH-2)	GAS FIRED WATER HEATER - A.O. SMITH BTH-150 WITH SEALED COMBUSTION CHAMBER, 100 GALLON GLASS LINED TANK, 150,000 BTU INPUT CAPACITY AND T&P RELIEF VALVE. OP. WEIGHT IS 1275#.	I-I/2"	I-I/2"		
W5-I)	WATER SOFTENER - PURE WATER PLUS RCI20-TMILM SIMPLEX UNIT WITH CONTROL SYSTEM WITH METERS 120-150,000 GRAINS EXCHANGE CAPACITY AND 18 GPM CONTIUOUS FLOW RATE AT 15 psi PRESSURE DROP (120/60/I).	I-I/2"	I-I/2"		

ORIGINAL DRAWING SIGNED BY: DWAYNE C. SUDWEEKS DATE ORIGINAL SIGNED: Feb 08, 2019 ORIGINAL ON FILE AT ENGINEERED SYSTEMS ASSOCIATES 1355 EAST CENTER, POCATELLO, IDAHO 83201



107 (10 002)	01
	Engineered Systems Associates
	AST CENTER D, IDAHO 83201
PHONE:	(208) 233-050

DRAWING NO.:

PROJECT NO, 18012 Date:

DRAWN BY: M JEHSEH

CHECKED BY:

D SUDWEEKS

FEBRUARY 2019

2 NEW ELEMENTARY SCHOOL FOR

COUNTY SCHOOL
ELEMENTARY SCHOOL
RIGBY, IDAHO JEFFERSON

III DDW architects D. a. R. P. L. R. N. N. I. R. G. Z. I. N. T. E. R. I. D. R. SCOTT L NIELSON, A.I.A. KEVIN R. BODILY, A.I.A. JAMES H WYATT, A.I.A.

PLUMBING FIXTURE SCHEDULE

2-12-19 CONSTRUCTION SET

FAX: (208) 233-0529 EMAIL: esa@engsystems.com