

2 PLUMBING FLOOR PLAN SCALE: 1/4" = 1'-0"

PLAN NOTES

- (1.) NEW GAS WATER HEATER TO BE SUPPLIED BY OWNER. EXTEND HW & CW LINES IN NEW CEILING FUR-OUT AS REQUIRED. SEE DETAIL ON SHEET P2.1.
- 2. CONTRACTOR TO SAWCUT EXISTING CONCRETE SLAB AS REQUIRED FOR NEW FLOOR DRAIN LOCATION.
- $\langle \underline{\mathfrak{3}}. \rangle$ MODIFY WASTE, WATER, & VENT FOR NEW SINK.
- 4. INSTALL WATER SOFTENER ROUGH IN LOOP IN COLD WATER MAIN ADJACENT TO WATER HEATERS FOR FUTURE WATER SOFTENER. SEE DETAIL F ON SHEET P2.1.
- 5. RUN NEW WASTE LINE UNDER SLAB TO NEAREST WASTE LINE AS SHOWN. FEILD VERIFY ELEVATION & ROUTE OF NEAREST 4". RISE NEW VENTS IN WALL TO NEAREST VTR. FEILD VERIFY EXISTING SIZE AND LOCATION OF EXISTING VTR.

<u>{6</u>.

<u>\9</u>.

- EXISTING GREASE TRAP. PROTECT DURING CONSTRUCTION. PROVIDE NEW FLOOR DRAIN STRAINER AFTER WORK IS COMPLETE. RAISE STRAINER FOR NEW FLOOR LEVEL AS REQUIRED.
- ISLAND SINKS TO BE VENTED AS PER DETAIL D/P2.1.

NEW HOT WATER LOOP TO BE PROVIDED & INSTALLED WITH RECIRC PUMP. FIELD VERIFY EXISTING ROUTE OF HOT WATER LOOP. SEE DETAIL ON SHEET C/P2.1.

SAW CUT FLOOR FOR NEW WASH BOX LOCATION. RUN NEW 1/2" CW & HW FROM NEAREST IN CEILING SPACE.

GENERAL NOTES

- 1. THE CONTRACTOR SHALL CHECK AND VERIFY ALL DIMENSIONS AND CONNECTIONS ON THE JOB SITE. ALL WORK SHALL BE EXECUTED FROM MEASUREMENTS TAKEN AT THE SITE.
- 2. THE MECHANICAL CONTRACTOR SHALL BE RESPONSIBLE TO INSURE PROPER CODE CLEARANCES FOR ELECTRICAL AND MECHANICAL ACCESS WHEN INSTALLING ANY EQUIPMENT SUPPLIED BY THE MECHANICAL CONTRACTOR.
- 3. IT IS CRITICAL THAT THIS CONTRACTOR COORDINATE EQUIPMENT LOCATIONS WITH PIPING, DUCTWORK, ELECTRICAL CONDUIT AND BUILDING STRUCTURE TO INSURE CODE COMPLIANCE.
- 4. CEILING DIFFUSERS ARE SHOWN IN APPROXIMATE LOCATIONS. REFER TO LIGHTING PLANS AND REFLECTED CEILING PLAN FOR EXACT LOCATIONS.
- 5. DUCT DIMENSIONS CALLED OUT ON DRAWINGS ARE INSIDE FREE AREA DIMENSIONS. ACOUSTICAL DUCT LINER ARE TO BE ADDED TO OVERALL MEASUREMENTS.
- 6. ALL DUCTWORK AND PIPING WHICH PASSES THRU FIRE RATED WALLS TO BE FIRE STOPPED WITH APPROVED FOAM OR SEALANT. REFER TO SPECIFICATIONS FOR APPROVED MANUFACTURES.



GPCARChiteCts 18 N. Main St., Ste. 200 Driggs, Idaho 83422 208.354.8036 www.gpcarchitects.com

Ownership & Use of Documents Drawings and specifications, as instruments of professional service are and shall remain the property of the architect. These documents are not to be used in whole or in part for any project or purposes whatsoever, without the prior specific written authorization of GPC Architects PLLC.

 \mathcal{O}

ш

S

revisions

project:

sheet:

no. description

DPW project: 19230

date: 04/17/2019

PLUMBING

FLOOR PLAN

P1.1

ADDENDUM #1 5/17/19

1806

Ш

 \cap

0

Ш

C

Ш

Ш

 \square

 \square

0

Σ

Ц

date